

KDT KE-706GBSUT Laser Edgebander-



The KE-706 GBSUT Laser 3.0 Edgebander offers affordable processing of laser tape with a genuine laser unit.

Switch effortlessly between laser tape and standard tape at the press of a button.

Stay ahead of your competition and enjoy the benefits of this fully loaded, auto-adjustable, industrial-level laser and glue Edgebander.

Auckland

19 Allens Road, East Tamaki
Auckland 2013
Ph (09) 271 7700
Fax (09) 271 7728

Christchurch

159 Ferry Road, Waltham
Christchurch 8011
Ph (03) 366 2013
Fax (03) 366 2021

Call free: 0800 522 577

Copyright © 2024 W & R Jack Limited.



KDT KE-706GBSUT Laser Edgebander-



Overview and features

- Anti-adhesive spray unit prior to Pre-milling
- Top Belt Pressure Beam - Servo Adjustable
- Solid Polished Steel Infeed Fence - Servo Adjustable
- Pre-Milling Unit with Diamond Tooling
- Gravity Fed Quick-Change EVA Hot-Melt Glue Application Unit
- Dedicated Pressure Zone for Standard Tape - Servo Adjustable
- Laser Unit for Processing Laser tape
- Dedicated Pressure Zone for Laser Tape - Servo Adjustable
- End Trimming Unit
- Rough Trim Trimming Unit
- Fine Trim Trimming Unit - Servo Adjustable
- 2 Motor Corner Rounding Unit - 2-Point Pneumatic Adjustment
- Multi-Profile Top & Bottom Radius Scraping Unit - Servo Adjustable
- Flat Surface Scraping Unit
- Detergent Spray Unit
- First Buffing Unit
- Second Buffing Unit

Specifications

Weight	4000kg
Feed speed	15, 18 & 24m/min
Tape thickness	0.4 - 3mm (0.8 - 3mm laser)
Panel thickness	9 - 60mm

Specifications are subject to change without notice.

