

Virutex PEB Zero line Edgebander-



Auckland
19 Allens Road, East Tamaki
Auckland 2013
Ph (09) 271 7700
Fax (09) 271 7728

Christchurch
159 Ferry Road, Waltham
Christchurch 8011
Ph (03) 366 2013
Fax (03) 366 2021

Call free: 0800 522 577
Copyright © 2024 W & R Jack Limited.



Virutex PEB Zero line Edgebander-



Compact Design, Stable Temperature, With a 40% higher adhesion than conventional hot-melt coating

Compact design Portable Edgebanding machine with ZeroLine® technology by hot air. Thanks to this technology the banding between the panel and the tape is excellent, with a seamless joint. The result is an edgebanding of high quality.

Excellent finishing on straight, round, shaped and inclined panels. Very practical for small or medium manufacturing series due to its easy operation and fast adjustment.

For PVC & ABS tapes with coextruded or postprocessed active layer, so it is not necessary to clean a glue tank. For tapes up to 2 mm thickness. It is possible to band acrylic and lacquered boards.

Perfect finishing on straight, round, shaped and inclined panels (0°- 50°).

The PEB works with low pressure air. It does not need a high performance compressed air system. With light indicator of optimal working temperature reached. Equipped with roller holder.

The edge banding machines with hot air technology fuse the edge to the panel, providing an excellent finish and seamless joint.

ZeroLine® is a registered trademark of Virutex.

Auckland

19 Allens Road, East Tamaki
Auckland 2013
Ph (09) 271 7700
Fax (09) 271 7728

Christchurch

159 Ferry Road, Waltham
Christchurch 8011
Ph (03) 366 2013
Fax (03) 366 2021

Call free: 0800 522 577


Copyright © 2024 W & R Jack Limited.



Virutex PEB Zero line Edgebander-



Excellent finishing on straight, round, shaped and inclined panels (0°- 50°)



Excellent finishing on straight, round, shaped and inclined panels (0°- 50°)



Excellent finishing on straight, round, shaped and inclined panels (0°- 50°)

Overview and features

Specifications

Feed speed	1.0 - 3.3 m/min
Working temperature	max: 370° C
Tape width	10 - 65 mm
Tape thickness	0.8 - 2.0 mm
Weight	11.5kg
Dimensions (W x D x H)	230x212x360 mm
Air pressure	6 bar

Specifications are subject to change without notice.

Auckland
19 Allens Road, East Tamaki
Auckland 2013
Ph (09) 271 7700
Fax (09) 271 7728

Christchurch
159 Ferry Road, Waltham
Christchurch 8011
Ph (03) 366 2013
Fax (03) 366 2021

Call free: 0800 522 577
Copyright © 2024 W & R Jack Limited.

