Mafell A 18 Cordless Drill Driver PURE in T-MAX-





The all new generation drill driver A 18 from Mafell. In difficult situations the impulse mode delivers a critical boost, e.g. for releasing immovable screws or controlling the first few turns when drilling into smooth surfaces. With 4 magnetic bit holders on both sides of the battery holder, the desired bit is always to hand.

*Battery is not included

Delivery specification:

Cordless Drill Driver A 18:

1 cordless drill driver A 18

1 quick-release chuck A SBF 13

1 quick-release bit holder A-SBH

1 belt clip

1 auxiliary handle

PURE in T-MAX



Mafell A 18 Cordless Drill Driver PURE in T-MAX-





Spirit levels

Two spirit levels clearly indicate the 90° angle when driving screws and drilling, horizontally and vertically



Powerful 18V

More powerful than its predecessors, the 18V machines make light work of drilling even 68mm holes with an Auger bit in wood



Anti-kickback

The electronic anti-kickback function provides extra safety by actively shutting down the motor and protecting the wrist against sudden twisting

Overview and features

The all new generation drill driver A 18 from Mafell

- In difficult situations the impulse mode delivers a critical boost, e.g. for releasing immovable screws or controlling the first few turns when drilling into smooth surfaces.
- With 4 magnetic bit holders on both sides of the battery holder, the desired bit is always to hand.
- Bright LED lamps with an afterglow effect illuminate a large working area.
- Bits and push-fit accessories are inserted directly in the ¼" drive.
- 43 mm diameter clamping collar fits all MAFELL BST drilling stations.
- To overcome the toughest challenges, we have given the new-generation A 18 an especially rugged specification and extra power.



Mafell A 18 Cordless Drill Driver PURE in T-MAX-



Specifications

Voltage rating 18V Weight 1.2kg

Technical data:

Collar diameter 43 mm
Chuck capacity 13 mm
Max. drilling diameter in wood / steel 68 / 13 mm
Torque soft / hard 65 / 130 Nm
Impulse torque (soft) 65 Nm
1st speed range 0 - 560 1/min

 1st speed range
 0 - 560 1/min

 2nd speed range
 0 - 1960 1/min

 Dimensions (L x W x H)
 145 x 79 x 201 mm

Nominal voltage 18 V Torque settings 10 + 1 Vibration (measured in metal/reinforced concrete) < 2,5/- m/s^2

Noise level dB(A) 73 Sound power level (LwA) dB(A) 88 Weight 1,2 kg

Specifications are subject to change without notice.

