Mafell ASB 18 Cordless Impact Drill Driver PURE in T-MAX-





Mafell ASB 18 Cordless Impact Drill Driver PURE in T-MAX-



The all new generation cordless Impact drill driver ASB 18 from Mafell

- Drilling
- Driving
- · Percussion drilling

Capable in dealing with the toughest challenges, the new-generation A 18 and ASB 18 has an especially rugged specification and extra power. addition of the Impact drill function makes the ASB 18 a genuine all-rounder. By applying the MAFELL ErgoBalance design principle, ease of use and fatigue-free operation is priotised.

*Battery is not included

Delivery specification:

- 1 Quick-release chuck A-SBF 13; Ref. No. 206772
- 1 Quick-release bit holder A-SBH; Ref. No. 206766
- 1 Belt clin
- 1 Auxiliary handle
- Transport and storage box T-MAX



Mafell ASB 18 Cordless Impact Drill Driver PURE in T-MAX-





Powerful impact drill functionality

Delivers excellent results when drilling holes in masonry



Spirit levels

Two spirit levels clearly indicate the 90° angle when driving screws and drilling, horizontally and vertically



Anti-kickback

The electronic anti-kickback function provides extra safety by actively shutting down the motor and protecting the wrist against sudden twisting

Overview and features

Its impact drill function makes the ASB 18 a genuine all-rounder

- In difficult situations the impulse mode delivers a critical boost, e.g. for releasing immovable screws or controlling the first few turns when drilling into smooth surfaces.
- With 4 magnetic bit holders on both sides of the battery holder, the desired bit is always to hand.
- Bright LED lamps with an afterglow effect illuminate a large working area.
- $\bullet\,$ Bits and push-fit accessories are inserted directly in the $1\!\!/4"$ drive.
- 43 mm diameter clamping collar fits all MAFELL BST drilling stations.
- To overcome the toughest challenges, we have given the new-generation A 18 an especially rugged specification and extra power.



Mafell ASB 18 Cordless Impact Drill Driver PURE in T-MAX-



Specifications

Voltage rating 18V Weight 1.3kg

Technical data:

Collar diameter 43 mm
Chuck capacity 13 mm
Max. drilling diameter in wood / steel 68 / 13 mm
Torque soft / hard 65 / 130 Nm
Impulse torque (soft) 65 Nm
1st speed range 0 - 560 1/min

2nd speed range 0 - 560 1/min
2nd speed range 0 - 1960 1/min
Dimensions (L x W x H) 163 x 79 x 201 mm

Nominal voltage 18 V

Impact rate 38000 1/min Torque settings 10 + 1

Vibration (measured in metal/reinforced concrete) < 2,5/15,5 m/s^2

Noise level dB(A) 92
Sound power level (LwA) dB(A) 103
Weight 1,3 kg

Specifications are subject to change without notice.

