





A unique mix of technology, tradition and quality.

With a large cutting height and high operating comfort the Felder K 740 S sliding table panel saw combines both precision and power in a compact design.

This high-quality panel saw features a powerful circular saw unit with a maximum cutting height of 140 mm when using a \emptyset 400 mm saw blade. For even greater versatility, an optional electrically driven scoring unit with a \emptyset 120 mm blade can be used in combination with a \emptyset 350 mm main saw blade—ensuring smooth, tear-free cuts.

A tilting saw blade unit and precision double-guiding system for accurate angle and height adjustments, the K 740 S sets a new standard for efficiency. The solid outrigger tables, available on both the Professional and S models, provide superior support for handling large panels with ease. Additionally, the X-Roll format sliding table, protected from dust and maintenance-free, guarantees years of flawless operation.

For enhanced safety and dust extraction, the K 740 S is equipped with a tilting Felder overhead saw guard. The optional "Power-Drive" package offers electronic saw blade height and angle adjustments accurate to a tenth of a millimeter, ensuring unmatched precision and convenience in your workshop.

Experience a new level of efficiency and precision with the FELDER K 740 S – the perfect solution for professional woodworking.

Please note machine images may show optional equipment.







'X-Roll' sliding table

The continuously developed linear guiding system from Felder has been astounding woodworkers since 1990. The high quality sliding table guiding technology, 'X-Roll,' offers amazing operating smoothness and is completely maintenance free. The 'x' design of the position of the roller bearings ensures that they move smoothly along hardened guides.



'Easy-Glide' system

A highly robust synthetic material located in the guidance track of the tilting brackets ensures they run smoothly, and are maintenance free even under the most extreme conditions. The tilt guide segment runs without lubrication and is insensitive to dust.



Advanced circular saw unit

The advanced circular saw unit with the patented tilt segment "Easy-Glide" impresses with a cutting height of 140 mm when using a Ø 400 mm saw blade. The electric scoring unit for scoring blades with a diameter of 120 mm can be used in combination with a Ø 350 mm saw blade.

Overview and features





Specifications

Motor 5.5kW (7.5hp) 3 phase

Weight850kgMax. saw blade Ø400mmMaximum cutting height104mmSaw blade speed4800rpmWorking height890mmSliding table length2800mmCrosscut fence length2600mmOutrigger table size1500mm

Specs shown are for the standard model we offer, but Felder offer a wide variety of options, so talk to us about customising a machine to suit you.

Specifications are subject to change without notice.

